

For Office Use ONLY:

Amount Paid _____

CURB CUT/DRIVEWAY REPLACEMENT PERMIT

To be used to have curb cut or replaced

2828 Allouez Avenue Bellevue, WI 54311 (920) 468-5225 FAX (920) 569-1876


	PLACE 10			
Locatio	on Address	Residen	itial Commercial	
Number of Driveways				
Building Contractor				
Buildir	g Contractor Email			
Concrete Contractor		Phone #	Phone #	
Gener	al Requirements & Condit	s:		
 Any contractor working in the Village Right-Of-Way shall provide the Village with a certificate of Insurance. All Curb cuts must be inspected when the forming is completed and prior to pouring of concrete. No residential driveway shall exceed the following width at the curb line unless approved by the Public Works Director: a. Single Driveway 17' b. Double Driveway 30' c. Duplex Center 40' d. Duplex End Garage 25' Commercial driveway widths/curb openings per approved site plans. If driveway replacement is within 3 feet of expansion/contraction joint, the curb section must be removed to said joints. Concrete shall be 6 bag mix minimum, with 6% minimum air entraining. Apron and sidewalk sections shall be 6" thick. Recommended that concrete is sealed per industry standards. Concrete will be the only acceptable material to form any portion of the curb section. Upon signing of curb cut permit, applicant hereby warrants curb replacement for a period of two (2) years from the date of permit. Curb cut inspections must be made during regular working hours. Monday thru Friday-7:30A.M.to 3:30 P.M. It shall be the responsibility of the owner-builder to maintain property stakes at all times Proper barricades, flags, warning signals and flagmen, if necessary, shall be provided by the applicant to safeguard the public. All dramages to the road surface, shoulders, slopes, ditches, curb and gutter, etc. shall be restored to a condition acceptable to the Village of Bellevue at the sole cost and expense of the applicant. The proposed construction and the exercise of this permit shall conform to all requirements set forth in the Ordinances of the Village of Bellevue and to any regulations set forth by any legally constituted body having j				
Applicant Signature				
	C	☐ APPROV	/ED □ DENIED	
Inspect	ed Bv			

Date Paid __

Receipt # _____

NOTES:

Minimum Height Of Sidewalk Shall Be Calculated at 4" Per Foot From Back Of Curb (At Full Curb Height) To Back Of Sidewalk Plus One Inch



Max D=12', Max CO=17'

Double Width Residential

Max D=25', Max CO=30'

Commercial One Way

Max D=20', Max CO=30' Or As Shown On Approved Site Plan

Commercial Two Way

Max D=25', Max CO=35' Or As Shown On Approved Site Plan

COMMERCIAL

CO = D+10' Or Site Plan Dimension

RESIDENTIAL

CO = D+5' Or Site Plan Dimension

NOTES:

- 1. Driveway Entrance and Sidewalk Shall Be 6" Thick, Min. 6 Bag Mix
- 2. 6% Min. Air Entrainment
- 3. If Any Expansion Joint Is Within 3 Feet of Driveway Construction, The Curb Shall Be Removed To The Joint. Dowel The New Curb Into The Existing With NO. 4 Bars, 4' Long

